



US009637018B2

(12) **United States Patent**  
**Li et al.**

(10) **Patent No.:** **US 9,637,018 B2**  
(45) **Date of Patent:** **May 2, 2017**

(54) **ROAD FOR CHARGING ELECTRIC VEHICLE**

(71) Applicants: **Ka Fat Li**, Hong Kong (HK); **Kwok Wah Pun**, Hong Kong (HK)

(72) Inventors: **Ka Fat Li**, Hong Kong (HK); **Kwok Wah Pun**, Hong Kong (HK)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 120 days.

(21) Appl. No.: **14/804,356**

(22) Filed: **Jul. 21, 2015**

(65) **Prior Publication Data**

US 2016/0031337 A1 Feb. 4, 2016

(30) **Foreign Application Priority Data**

Jul. 29, 2014 (CN) ..... 2014 2 0422312 U

(51) **Int. Cl.**

**H02J 7/00** (2006.01)  
**B60M 1/00** (2006.01)  
**H02G 5/04** (2006.01)  
**B60M 1/18** (2006.01)  
**B60M 1/30** (2006.01)  
**B60L 11/18** (2006.01)  
**B60L 5/40** (2006.01)  
**B60L 5/38** (2006.01)  
**B60L 5/39** (2006.01)  
**B60M 1/34** (2006.01)

(52) **U.S. Cl.**

CPC ..... **B60L 11/1824** (2013.01); **B60L 5/38** (2013.01); **B60L 5/39** (2013.01); **B60L 5/40** (2013.01); **B60L 11/1816** (2013.01); **B60M 1/34** (2013.01)

(58) **Field of Classification Search**

CPC ..... B60L 11/1824  
USPC ..... 320/107, 109; 191/13, 22 C, 33 R, 35, 191/39

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,129,203 A \* 12/1978 Berman ..... B60L 5/36  
104/145  
7,600,621 B2 \* 10/2009 Lohr ..... B60L 5/40  
104/140  
7,748,509 B2 \* 7/2010 Donnard ..... B60L 5/40  
104/140  
8,763,773 B2 \* 7/2014 Asplund ..... B60L 5/40  
191/22 C  
9,199,541 B2 \* 12/2015 Asplund ..... B60L 5/42

\* cited by examiner

*Primary Examiner* — Richard V Muralidar

(57) **ABSTRACT**

Disclosed is a road for charging electric vehicle. The road includes an electrified rail which includes an electrode plate for connecting an electric plate of the electric vehicle, an insulated cover covering on the plate electrode so as to prevent electric leakage and a neutral layer covering on the insulated cover for connecting a neutral electrode plate of the electric vehicle. The electrode plate includes a first electrode plate and a second electrode plate. The first electrode plate is disposed above the second electrode plate and between the first electrode plate and the second electrode plate there is a gap so that the electric plate of the electric vehicle is able to be sandwiched between the first electrode plate and the second electrode plate while charging. According to the present invention, the road surface is provided with electrified rail, thus the electric vehicle can charge while driving.

**20 Claims, 10 Drawing Sheets**

